
























# TECHNICAL CHARACTERISTICS

ambra		Covering type according to EN ISO 10582: Heterogeneous resilient-flooring to glue		wineo
	<b>ambra wood</b>	<b>ambra stone</b>		
<b>Format</b>	1200 x 180 mm	609.6 x 304.8		
<b>Product thickness</b>	2 mm	2 mm		
<b>Planks, tiles / m<sup>2</sup> per box</b>	18 / 3.89 m <sup>2</sup>	18 / 3.34 m <sup>2</sup>		
<b>Boxes / m<sup>2</sup> per pallet</b>	60 / 233.40 m <sup>2</sup>	72 / 240.48 m <sup>2</sup>		
<b>Guarantee</b>	15 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de			
<b>Classification</b>			<b>Product composition</b>	
	<b>Utilization class 23</b> Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices	1	<b>Surface sealing</b>
	<b>Utilization class 31</b> Medium use in the commercial sector EN ISO 10874	Hotel rooms, small offices	2	<b>Wear layer</b> Thickness 0.3 mm
	<b>Wear resistance</b> EN 660-2	Group T	3	<b>Decor film</b> Surface texture - various embossings
	<b>Reaction to fire</b> EN 13501-1	B <sub>fl</sub> - s1	4	<b>Base layer</b>
	<b>Anti slip category</b> DIN 51130	R 9	5	<b>Backing</b>
	<b>Slip resistance</b> EN 13893	μ ≥ 0.30 - DS		<b>DESIGN FLOORING to glue</b> 
	<b>Anti-static properties</b> EN 1815	≤ 2 kV		
	<b>Staining and chemical resistance</b> EN ISO 26987	Good resistance according to the concentration and residence time	<b>Certifications</b>	
	<b>Light fastness</b> EN ISO 105-B02	≥ 6	 <p>windmüller flooring products WFP GmbH Nord-West-Ring 21 D-32832 Augustdorf</p> <p>- 07 - <b>Elastischer Bodenbelag</b> DOP: 0401/001 EN 14041:2004</p>  <p>Resilient Flooring to be used within a building.</p> <p><b>EMISSIONS DANS L'AIR INTÉRIEUR</b></p>  <p>Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)</p>  <p>Schadstoffgeprüft Emissionsgeprüft</p>  <p>PROFI 70 710 691-1</p>  <p>100% Phthalate free</p> <p><b>factory made coated</b></p>	
	<b>Residual indentation</b> EN ISO 24343-1	~ 0.02 mm		
	<b>Castor chair test</b> EN 425 / ISO 4918	Type W – no visible change		
	<b>Thermal resistance</b> EN 12667	~ 0.01 (m <sup>2</sup> K)/W		
	<b>Impact sound reduction</b> EN ISO 16251-1	~ 4 dB		
	<b>Dimension stability</b> EN ISO 23999	~ 0.15 %		
	<b>Disposal</b>	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		

### Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.