

LA MANGA

Kleuren	Coloris	Farben	Colours
9607 L.Brown	*	9633 L.Blue	*
9613 L.Beige	*	9639 Navy	*
9614 D.Beige	*	9647 D.Green	
9615 Mink	*	9653 Terre	*
9616 Autumn	*	9659 Wine	*
9617 Mocca	*	1714 Beige	
9618 Cognac	*	1718 Chocolate	
9619 Tobacco	*	1745 Green	*
9622 Silver	*	1735 Blue	*
9623 Grey	*	9630 Black	*
9628 Anthracite	*		
9629 Charcoal	*		

* = 500 cm. english collection

<u>Fabricagemethode</u>	<u>Méthode de fabrication</u>	<u>Herstellungsverfahren</u>	<u>Manufacturing process</u>
Getuft 5/32" lussen pool	Tuftée 5/32" bouclé	Getufted 5/32" Schlinge	Tufting 5/32" loop-pile
<u>Poolsamenstelling</u>	<u>Composition du velours</u>	<u>Polmaterial</u>	<u>Pile content</u>
100% polypropylene	100% polypropylene	100% polypropylene	100% polypropylene
<u>Tuftdoek</u>	<u>Support</u>	<u>Trägermaterial</u>	<u>Primary backing</u>
Geweven PP	Tissé PP	PP Gewebe	Woven PP
<u>Rug</u>	<u>Dossier</u>	<u>Rückenausrüstung</u>	<u>Secondary backing</u>
A.B. + Vlies	A.B. + Feutre	A.B. + Vlies	A.B. + Felt
<u>Poolgewicht</u>	<u>Poids du velours</u>	<u>Polgewicht</u>	<u>Pile weight</u>
ca. 400 gr/m2.	ca. 400 gr/m2.	ca. 400 gr/m2.	ca. 400 gr/m2.
<u>Totaalgewicht</u>	<u>Poids total</u>	<u>Gesamtgewicht</u>	<u>Total weight</u>
A.B. : ca. 1430 gr/m2. Vlies : ca. 1470 gr/m2.	A.B. : ca. 1430 gr/m2.. Feutre: ca. 1470 gr/m2.	A.B. : ca. 1430 gr/m2. Vlies : ca. 1470 gr/m2.	A.B. : ca. 1430 gr/m2. Felt : ca. 1470 gr/m2.
<u>Poolhoogte</u>	<u>Hauteur du poil</u>	<u>Polhöhe</u>	<u>Pile height</u>
ca. 4 mm.	ca. 4 mm.	ca. 4 mm.	ca. 4 mm.
<u>Totale hoogte</u>	<u>Hauteur total</u>	<u>Gesamthöhe</u>	<u>Total height</u>
A.B. : ca. 6 mm. Vlies : ca. 8 mm.	A.B. : ca. 6 mm. Feutre: ca. 8 mm.	A.B. : ca. 6 mm. Vlies : ca. 8 mm.	A.B. : ca. 6 mm. Felt : ca. 8 mm.
<u>Aantal noppen</u>	<u>Nombre de points</u>	<u>Noppenzahl</u>	<u>Number of knots</u>
ca. 96.330 m2.	ca. 96.330 m2.	ca. 96.330 m2.	ca. 96.330 m2.
<u>Breedte</u>	<u>Largeur</u>	<u>Breite</u>	<u>Width</u>
400 cm. + 500 cm. *	400 cm. + 500 cm. *	400 cm. + 500 cm. *	400 cm. + 500 cm. *
<u>Aantal kleuren</u>	<u>Nombre de coloris</u>	<u>Farbenzahl</u>	<u>Number of colours</u>
22	22	22	22
<u>Lichtechtheid</u>	<u>Résistance à la lumière</u>	<u>Lichtechtheit</u>	<u>Light fastness</u>
ISO 105 B02: 5 tot 8	ISO 105 B02: 5 à 8	ISO 105 B02: 5 bis 8	ISO 105 B02: 5 to 8
<u>Waterrechtheid</u>	<u>Résistance à l'eau</u>	<u>Wasserechtheit</u>	<u>Water resistance</u>
EN 1307, annex F: 5	EN 1307, annex F: 5	EN 1307, annex F: 5	EN 1307, annex F: 5
<u>Vlamwerend BS4790</u>	<u>Tenue au feu BS4790</u>	<u>Brennverhalten BS4790</u>	<u>Combustibility BS4790</u>
A.B. : Low Radius of Ignition Felt : Medium Radius of Ignition	A.B. : Low Radius of Ignition Feutre: Medium Radius of Ignition	A.B. : Low Radius of Ignition Vlies : Medium Radius of Ignition	A.B. : Low Radius of Ignition Felt : Medium Radius of Ignition
<u>Bijzonderheden</u>	<u>Caractéristiques</u>	<u>Besonderheiten</u>	<u>Characteristics</u>
A.B. DOP Nr. 1058-114996 A.B. GUT 89ECF791 Felt DOP Nr. 1058-114167 Felt GUT 25FD25DE	- - -	- - -	- - -