
























# TECHNICAL CHARACTERISTICS

select		Covering type according to EN ISO 10582: Heterogeneous resilient-flooring to glue		wineo
	<b>select wood</b>	<b>select stone</b>		
<b>Format</b>	1200 x 180 mm	900 x 450 mm		
<b>Product thickness</b>	2.5 mm	2.5 mm		
<b>Planks, tiles / m<sup>2</sup> per box</b>	15 / 3.24 m <sup>2</sup>	10 / 4.05 m <sup>2</sup>		
<b>Boxes / m<sup>2</sup> per pallet</b>	60 / 194.40 m <sup>2</sup>	50 / 202.50 m <sup>2</sup>		
<b>Guarantee</b>	25 years – Guarantee for private use according to Windmüller warranty conditions – <a href="http://www.wineo.de">www.wineo.de</a>			
<b>Classification</b>				
	<b>Utilization class 23</b> Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices	1	<b>Surface sealing</b>
	<b>Utilization class 33</b> Heavy-duty use in the commercial sector EN ISO 10874	Department stores, lobby's, schools, open plan offices, corridors	2	<b>Wear layer</b> Thickness 0.55 mm
	<b>Utilization class 42</b> Normal use in the light industrial sector EN ISO 10874	Storage rooms, workshops	3	<b>Decor film</b> Surface texture - various embossings
	<b>Wear resistance</b> EN 660-2	Group T	4	<b>Base layer</b>
	<b>Reaction to fire</b> EN 13501-1	B <sub>fl</sub> - s1	5	<b>Backing</b>
	<b>Anti slip category</b> DIN 51130	R 9		<b>DESIGN FLOORING to glue</b> 
	<b>Slip resistance</b> EN 13893	μ ≥ 0.30 - DS		Bevelled edge – select wood
	<b>Anti-static properties</b> EN 1815	≤ 2 kV		
	<b>Staining and chemical resistance</b> EN ISO 26987	Good resistance according to the concentration and residence time	<b>Certifications</b>	
	<b>Light fastness</b> EN ISO 105-B02	≥ 6	 <p>windmüller flooring products WFP GmbH Nord-West-Ring 21 D-32832 Augustdorf</p> <p><b>Elastischer Bodenbelag</b> DOP: 0401001 EN 14041:2004</p>  <p>Resilient Flooring to be used within a building.</p>  <p>Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)</p>  <p>TÜV RFI Schadstoffgeprüft Emissionsgeprüft</p> <p>PROFI GELB 10 310 4081-1</p>  <p>100% recyclé fabriqué</p> <p><b>factory made coated</b></p>	
	<b>Residual indentation</b> EN ISO 24343-1	~ 0.02 mm		
	<b>Castor chair test</b> EN 425 / ISO 4918	Type W – no visible change		
	<b>Thermal resistance</b> EN 12667	~ 0.01 (m <sup>2</sup> K)/W		
	<b>Impact sound reduction</b> EN ISO 16251-1	~ 4 dB		
	<b>Dimension stability</b> EN ISO 23999	~ 0.15 %		
	<b>Disposal</b>	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		

### Relevant information:

- R 9 Decor „Heavy Metal“ excluded.
- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.