


EasyLock 4.0		
Thickness (mm)		4.00
Wear Layer (mm)		0.30
Utilization Class		
Coating		PU with Ceramic Bead
Embossing		Natural
Bevelled		no
Fiberglass		yes
Plank Size		190 x 1210 mm
Sqm per Plank		0.229 m ²
Sqm per Pack		2.3 m ²
Pallet Packing		73.6 m ² / 32 packs
Planks per Pack		10 planks
Net Wt/Gross Wt per Pallet		680 kg / 730 kg
Impact Sound Insulation	ISO 717-2	5 dB
Chemical Resistance	EN 423	High Resistance
Residual Indentation	EN 433	≤ 0,06 mm
Dimensional Stability	EN 434	0,09%
Color Fastness to Light	EN 20105-B02	≥ 6
Slip Resistance	DIN 51130	R10
Wear Resistance	EN 660-2	Group T
Fire Rating	EN ISO 9239-1	Bfl-S1
Warranty for Domestic use		20 Years
Warranty for Commerical use (Light*)		5 Years

Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards.

Easylock itself can be completely recycled.

* Valid with Contesse underlay only.



1 Angle two planks into position

2 Slide the two lockstrips in place

3 Press down and lock in place to form a watertight seal