

SHERWOOD OAK



	Product information Produkt informatie	Produkt Daten Information produit		
	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	3,20 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,30 mm
	Width Breedte	Breite Largeur	EN 426	2m, 2,5m, 3m, 3,5m, 4m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	30m 35m 30m
	Total roll weight Totaal rolgewicht	Totaal Rolgewicht Poids total des rouleaux		115kg - 230kg
	Classification Classificatie	Klassifizierung Classification	EN 685	23
				31

	Technical information Technische informatie	Technische Daten Information technique		
	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable

SHERWOOD OAK

	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	≤ 0,35 mm
	Impact sound improvement Contactgeluidsisolatie	Trittschallschutz Isolation acoustique	EN ISO 717/2	ΔLw 19dB
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B _f S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	DIN 51130	



B.I.G. Floorcoverings
Rijksweg 442
8710 - Wielsbeke

06

EN 14041:2004

Expanded (cushioned) polyvinyl
chloride floor coverings (EN653)

Reaction to fire : Class Bfl/s1

Slipperiness : DS

Formaldehyde : E1

EN 653