




Desso Textile floor covering - Tiles


Tweed EcoBase™


Specification according to EN 1307


Type of manufacture	ISO 2424		Tufted 1/10 "					
Aspect	ISO 2424		Structured loop pile					
Dye method			Solution dyed					
Dimension	EN 994	cm x cm	50 x 50 / 19,68" x 19,68" (20 tiles per box)					
Primary backing	ISO 2424		Polyester fleece					
Secondary backing	ISO 2424		Desso EcoBase® * - Containing at least 70% C2C positively defined recycled content					
Pile fibre composition	ISO 2424		BCF Polyamide 6 and ECONYL® (ECONYL® is made from 100% regenerated content) **					
Total thickness	ISO 1765	mm	7.0	inch	0.3			
Effective pile thickness	ISO 1766	mm	3.5	inch	0.14			
Total mass	ISO 8543	g/m²	4400	oz/yd²	129.9			
Total pile mass	ISO 2424	g/m²	900	oz/yd²	26.6			
Effective pile mass	ISO 8543	g/m²	635	oz/yd²	18.7			
Pile density	ISO 8543	g/cm³	0.181	lb/in³	0.0065			
Number of tufts	ISO 1763	/dm²	1580	/yd²	132104			
Stroll test	ISO 6356	kV	≤ 2,0					
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10 ⁹					
Horizontal resistance	ISO 10965	Ohm						
Use classification	EN 1307		33 Commercial - heavy use					
Luxury rating	EN 1307		LC 3					
Dimensional stability	EN 986	%	≤ 0,2					
Impact sound reduction ΔL _w	ISO 10140	dB	24					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α _s	0.01	0.04	0.08	0.18	0.31	0.38
Noise reduction	ISO 354	α _w	0.20					
Thermal resistance	ISO 8302	m².K/W	0.064					
Flammability	EN 13501-1		Bfl - s1 (loose laid tested)					
Prodis - GUT	www.pro-dis.info		C5B6CED5					



 Manufactured by:
 Desso BV
 PO Box 169
 EN 14041
 0493-CPR-0002
 NL - 5140 AD Waalwijk




 Made with 100% Regenerated Nylon


 GUT


 Quality- and Environmental Management System Certification ISO 9001 & ISO 14001



* DESO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.desso.com

** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.desso.com.

Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings. Note: Desso reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www.desso.com

EN-20170503



THE ULTIMATE FLOORING EXPERIENCE

A Tarkett Company